

Quick Reference Air Spring Chart

AD-346
(151705)

Description	P/N	Customer Order # Sales/Replace Kit P/N	Max Ext. Height	Comp. Height	Max Dia.	Design Height	Air Fitting Size (NPTF)	Top Fastener	Bottom Fastener	Mtg. Hole Centers
SLEEVES										
Sleeve 3.0"	58988		8.0	3.6	3.25	5.0-6.0	1/8"	3/4" - 16	3/8" - 24	N/A
Sleeve 4.0"	58482	50254	7.0	2.4	4.6	4.0-6.0	1/8"	3/4" - 16	1/2" - 13	N/A
Sleeve 4.5***	58483	50255	6.25	2.6	5.1	4.0-5.75	1/8"	3/4" - 16	1/2" - 13	N/A
Sleeve 4.0"	58287	50269	8.75	3.1	4.6	5.5-7.5	1/8"	3/4" - 16	1/2" - 13	N/A
Sleeve 4.0***	58430	50208	8.75	3.3	4.6	5.0-8.0	1/8"	3/4" - 16	1/2" - 13	N/A
Sleeve 4.5***	58387	50260	6.75	2.6	5.1	4.0-6.0	1/8"	3/4" - 16	1/2" - 13	N/A
Sleeve 4.5"	58487	50256	6.8	2.4	5.1	4.0-6.0	1/8"	3/4" - 16	1/2" - 13	N/A
Sleeve 4.5***	58587	50262	7.75	3.3	5.1	4.5-7.0	1/8"	3/4" - 16	1/2" - 13	N/A
Sleeve 4.5"	58987	50259	7.75	3.1	5.1	4.5-7.0	1/8"	3/4" - 16	1/2" - 13	N/A
Sleeve 4.5"	58486		9.75	3.1	5.1	6.0-8.0	1/8"	3/4" - 16	1/2" - 13	N/A
Sleeve 4.0"	58586	50272	9.91	3.1	4.6	6.0-8.5	1/8"	3/4" - 16	1/2" - 13	N/A
Sleeve 4.0"	58786	50202	10.25	3.1	4.6	7.5-9.5	1/8"	3/4" - 16	1/2" - 13	N/A
Sleeve 4.5"	58571	50203	10.25	3.1	5.1	6.5-8.5	1/8"	3/4" - 16	1/2" - 13	N/A
Sleeve 5.0"	58471	50261	10.25	3.1	5.6	6.5-8.5	1/8"	3/4" - 16	1/2" - 13	N/A
Sleeve 5.0"	58688		7.75	3.1	5.6	5.0-7.0	1/8"	3/4" - 16	1/2" - 13	N/A
Sleeve 6.0"	58341	50200	10.9	4.4	6.8	7.0-8.6	1/8"	M20-2.5	M20-2.5	N/A
BELLOWS										
Bellows 1B-5	58103	50207	5.8	1.8	6.5	3.5-5.0	1/4"	3/8" - 16	3/8" - 16	1.75"
Bellows 1B-6	58407	50352/50252	7.1	1.9	7.0	4.0-6.0	1/8"	3/8" - 24	3/8" - 24	2.75"
Bellows 1B-6**	58736	50284	7.1	2.7	7.0	4.0-6.0	1/8"	3/8" - 24	3/8" - 24	2.75"
Bellows 1B-6 Ultimate**	58740		7.0	2.7	7.0	4.0"-6.0"	1/8"	3/8"-24	3/8"-24	2.75"
Bellows 1B-8	58124	50211	7.3	1.8	9.4	4.0-6.5	1/4"	3/8" - 16	3/8" - 16	2.75"
Bellows 2B-6, Reg.	58439	50351/50251	7.7	2.3	6.5	4.5-6.5	1/8"	3/8" - 24	3/8" - 24	2.75"
Bellows 2B-6, Reg. Ultimate**	58494		8.25	2.7	6.5	4.5"-6.5"	1/8"	3/8"-24	3/8"-24	2.75"
Bellows 2B-6, Ext.	58437	50301/50201	9.1	2.3	7.0	5.0-7.0	1/8"	3/8" - 24	3/8" - 24	2.75"
Bellows 2B-6, Ext.*	58401	50309	9.1	2.3	7.0	5.0-7.0	1/4"	3/8" - 24	3/8" - 24	1.75"
Bellows 2B-6, Ext. **	58491		9.1	2.7	7.0	5.0"-7.0"	1/8"	3/8"-24	3/8"-24	2.75"
Bellows 2B-6, Ext. Ultimate**	58496		9.0	2.7	7.0	5.0"-7.0"	1/8"	3/8"-24	3/8"-24	2.75"
Bellows 2B-6, Crimped on metal, single port	58343		10.5	2.8	7	5.5-7.5	1/2"	3/8"-16	3/8"-16	1.75" - Top Centered - Bottom
Bellows 2B-6, Crimped on metal, dual port	58352		10.5	2.8	7	5.5-7.5	1/2"	3/8"-16	3/8"-16	1.75" - Top Centered - Bottom
Bellows 2B-7, Ext.	58115	50329/50229	9.0	3.3	8.0	6.0-8.0	1/4"	3/8"-16	3/8"-16	2.75"
Bellows 2B-7, Crimped on metal, single port	58616		12.5	2.8	8	6.0-9.0	1/2"	3/8"-16	3/8"-16	2.75"
Bellows 2B-7, Crimped on metal, dual port	58628		12.5	2.8	8	6.0-9.0	1/2"	3/8"-16	3/8"-16	2.75"
Bellows 2B-8	58119		10.3	2.8	8.6	7.0-8.0	1/4"	3/8" - 16	3/8" - 16	2.75"
ROLLING LOBES										
Rolling Lobe, 1R9	58202	58202	11.8	3.2	9.25	6.0-7.5	1/4"	1/2" - 20 3/4" - 16	3/8" - 16	3.38" Top 2.125" Bottom
Rolling Lobe, 1R11	58204	58204	13.0	3.7	11.5	6.0-10.0	1/4"	3/4" - 16 1/2" - 13	1/2" - 13	6.2" Top 2.125" Bottom
TAPERED SLEEVE										
1TS5.0"	58130		9.5"	4.25"	5.4"	6.5-8.5	3/8"	3/8"-24	3/8"-16	2.75" - Top Centered - Bottom

* Replaces Firestone 255C

** Has internal jounce bumper.

NOTE: When ordering replacement bellows for kit numbers 57125 and 57131, the mounting stud, P/N 17210, is not included.