



# Quick Reference Air Spring Chart

Description	P/N	Customer Order # Sales/Replace Kit P/N	Max Ext. Height	Comp. Height	Max Dia.	Max Load @ 100 PSI	Design Height	Air Fitting Size (NPTF)	Top Fastener	Bottom Fastener	Mtg. Hole Centers
<b>SLEEVES</b>											
Sleeve 3.0"	58988		8.0	3.6	3.25	410	5.0-6.0	1/8"	3/4"-16	3/8"-24	N/A
Sleeve 4.0"	58482	50254	7.0	2.4	4.6	870	4.0-6.0	1/8"	3/4"-16	1/2"-13	N/A
Sleeve 4.5"	58483	50255	6.25	2.6	5.1	1022	4.0-5.75	1/8"	3/4"-16	1/2"-13	N/A
Sleeve 4.0"	58287	50269	8.75	3.1	4.6	780	5.5-7.5	1/8"	3/4"-16	1/2"-13	N/A
Sleeve 4.0"	58430	50208	8.75	3.3	4.6	858	5.0-8.0	1/8"	3/4"-16	1/2"-13	N/A
Sleeve 4.5"	58387	50260	6.75	2.6	5.1	1076	4.0-6.0	1/8"	3/4"-16	1/2"-13	N/A
Sleeve 4.5"	58487	50256	6.8	2.4	5.1	1065	4.0-6.0	1/8"	3/4"-16	1/2"-13	N/A
Sleeve 4.5"	58587	50262	7.75	3.3	5.1	915	4.5-7.0	1/8"	3/4"-16	1/2"-13	N/A
Sleeve 4.5"	58987	50259	7.75	3.1	5.1	935	4.5-7.0	1/8"	3/4"-16	1/2"-13	N/A
Sleeve 4.5"	58486		9.75	3.1	5.1	920	6.0-8.0	1/8"	3/4"-16	1/2"-13	N/A
Sleeve 4.0"	58586	50272	9.91	3.1	4.6	787	6.0-8.5	1/8"	3/4"-16	1/2"-13	N/A
Sleeve 4.0"	58786	50202	10.25	3.1	4.6	782	7.5-9.5	1/8"	3/4"-16	1/2"-13	N/A
Sleeve 4.5"	58571	50203	10.25	3.1	5.1	900	6.5-8.5	1/8"	3/4"-16	1/2"-13	N/A
Sleeve 5.0"	58471	50261	10.25	3.1	5.6	965	6.5-8.5	1/8"	3/4"-16	1/2"-13	N/A
Sleeve 6.0"	58341	50200	10.9	4.4	6.8	1680	7.0-8.6	1/8"	M20-2.5	M20-2.5	N/A
<b>BELLOWS</b>											
Bellows 1B-5	58103	50207	5.8	1.8	6.5	1555	3.5-5.0	1/4"	3/8"-16	3/8"-16	1.75"
Bellows 1B-6	58407	50252	7.1	1.9	7.0	2210	4.0-6.0	1/8"	3/8"-24	3/8"-24	2.75"
Bellows 1B-6**	58736	50284	7.1	2.7	7.0	2210	4.0-6.0	1/8"	3/8"-24	3/8"-24	2.75"
Bellows 1B-6 Ultimate**	58740		7.0	2.7	7.0	2210	4.0"-6.0"	1/8"	3/8"-24	3/8"-24	2.75"
Bellows 1B-8	58124	50211	7.3	1.8	9.4	3340	4.0-6.5	1/4"	3/8"-16	3/8"-16	2.75"
Bellows 2B-6, Reg.	58439	50351/50251	7.7	2.3	6.5	2025	4.5-6.5	1/8"	3/8"-24	3/8"-24	2.75"
Bellows 2B-6, Reg. Ultimate**	58494		8.25	2.7	6.5	2025	4.5"-6.5"	1/8"	3/8"-24	3/8"-24	2.75"
Bellows 2B-6, Ext.	58437	50301/50201	9.1	2.3	7.0	2270	5.0-7.0	1/8"	3/8"-24	3/8"-24	2.75"
Bellows 2B-6, Ext.*	58401	50309	9.1	2.3	7.0	2270	5.0-7.0	1/4"	3/8"-24	3/8"-24	1.75"
Bellows 2B-6, Ext. **	58491		9.1	2.7	7.0	2270	5.0"-7.0"	1/8"	3/8"-24	3/8"-24	2.75"
Bellows 2B-6, Ext. Ultimate**	58496		9.0	2.7	7.0	2270	5.0"-7.0"	1/8"	3/8"-24	3/8"-24	2.75"
Bellows 2B-6, Crimped on metal, single port	58343		10.5	2.8	7	2030	5.5-7.5	1/2"	3/8"-16	3/8"-16	1.75" - Top Centered - Bottom
Bellows 2B-7, Ext.	58115	50329/50236/ 50229	9.0	3.3	8.0	2585	6.0-8.0	1/4"	3/8"-16	3/8"-16	2.75"
Bellows 2B-7, Crimped on metal, single port	58616		12.5	2.8	8	3055	6.0-9.0	1/2"	3/8"-16	3/8"-16	2.75"
<b>BELLOWS - ProSeries</b>											
Bellows 1B-6, Ultimate Pro Series**	58940	86003	7	2.7	7	2210	4.0"-6.0"	1/8"	3/8"-24	3/8"-24	2.75"
Bellows 2B-6, Ext. Pro Series**	58937	86001	9.1	2.3	7	2270	5.0"-7.0"	1/8"	3/8"-24	3/8"-24	2.75"
Bellows 2B-6, Reg. Pro Series**	58939	86002	7.7	2.3	6.5	2025	4.5"-6.5"	1/8"	3/8"-24	3/8"-24	2.75"
Bellows 2B-6, Reg. Ultimate Pro Series**	58994	86004	8.25	2.7	6.5	2025	4.5"-6.5"	1/8"	3/8"-24	3/8"-24	2.75"
Bellows 2B-6, Ext. Ultimate Pro Series**	58996	86005	9	2.7	7	2270	5.0"-7.0"	1/8"	3/8"-24	3/8"-24	2.75"
<b>TAPERED SLEEVE</b>											
1TSS.0"	58130		9.5"	4.25"	5.4"	1216	6.5-8.5	3/8"	3/8"-24	3/8"-16	2.75" - Top Centered - Bottom
<p>* Replaces Firestone 255C  ** Has internal jounce bumper.  NOTE: When ordering replacement bellows for kit numbers 57125 and 57131, the mounting stud, P/N 17210, is not included.</p>											